

Durailless



IDEAL FOR: Transporters needing economical, flexible, light-weight bulkheads.

Features:

- Vinyl laminated skin on 5mm corrugated plastic with a 2" open cell foam core
- Ability to bend and flex when hit
- 25% lighter than the standard 3" construction, making the Duraflex easier to maneuver throughout the trailer
- · Entire exterior is easy to clean
- · Heavy duty reinforced web handles
- 10 Year Warranty against delamination of the core
- 60 mil UHMW Scuff Plate protects bottom from non-skid floors with 5 Year Warranty against wear



Insulated Transport Products www.insulatedtransportproducts.com 1.800.233.6180





Available Options



Fan Kit

As an alternative to a rear evaporator, the Two-Temp Fan Kit allows temperature control in the second compartment. Specifications include: 10" diameter; 10 prong blade; 12 volt, 6000 hour brush life motor; displacement of 650 CFM; temperature range from -40°F to +80°F, and an On/Off switch



Vent Kit

10" Diameter Vent with Adjustable Velcro Flap provides controlled air flow to rear compartment or return air flow when installed with a Fan Kit



Cold Draw Ventilation System

As an alternative to a rear evaporator, the Cold Draw is mounted in the upper corner of the trailer. Air is drawn into the center of the compartment by a 12 volt motor and distributed across the ceiling to maintain a constant temperature.



Two-Way Hinge

Webbing reinforced on top and bottom, the Two-Way Hinge allows entry from both compartments and prevents damage.



Abrasion Plate

Available 2' and 4' high, 100 mil HDPE offers protection from forklift and pallet damage. Installed with flush mounted hardware.





Tether Connect

Configure bulkhead(s) to be securely stored away in trailer by using part #TCA with roller tracks. Never lose a bulkhead again!

97-4505

Custom Labeling Up to 3" High

Identify your bulkhead with your company name and trailer number.



E or F Straps

Installed withflush mounted hardware and comes with a UHMW abrasion guard to protect against premature wear from the track,